

METHOD AND SYSTEM FOR AN AUTOMATED DEPARTURE STRATEGY

RELATED PATENT APPLICATION

This patent application is a continuation of U.S. Patent Application Serial No. 10/285,112, entitled *Method and System for an Automated Departure Strategy*, filed on
5 October 31, 2002, now U.S. Patent No. _____; which is co-pending with U.S. Patent Application Serial No. 10/285,597, entitled *Method and System for an Automated Disambiguation*, filed on October 31, 2002.

10

TECHNICAL FIELD OF THE INVENTION

The present invention relates generally to telecommunications systems, and more specifically relates to a method and system for an automated departure
15 strategy.

BACKGROUND OF THE INVENTION

In order to decrease costs and increase efficiency, telephone companies are automating directory assistance systems. An early step toward automation of directory assistance was the use of store and forward technology to assist live operators. A caller was asked for a locality by a pre-recorded prompt. The store and forward system stored a compressed version of the caller's response to the prompt, and brought a live operator onto the line. The operator heard the compressed version of the response and then completed the remaining dialogue with the caller to provide a unique telephone number.

With the advent of speech recognition, companies have begun adding speech recognition capabilities to directory assistance systems. Automated speech recognition recognizes a locality from the caller's response to a prompt for locality. In a typical system, if the speech recognition is successful, the system prompts the caller for the listing name, puts an operator on the line, populates the operator's workstation display with the recognized locality, and plays a recorded compressed version of the caller's response to the listing question. The operator then conducts the remaining dialogue, searches for the listing, and provides the unique telephone number to the caller. But directory assistance is not totally automated and operator involvement is still required in providing the callers telephone numbers.

BRIEF DESCRIPTION OF THE DRAWINGS

A more complete understanding of the present
embodiments and advantages thereof may be acquired by
referring to the following description taken in
5 conjunction with the accompanying drawings, in which like
reference numbers indicate like features, and wherein:

FIGURE 1 depicts a block diagram of an automated
directory assistance system;

10 FIGURES 2A and 2B illustrate a flow diagram of a
method for the automated disambiguation of search results
and automated defaulting to an operator in the directory
assistance system;

FIGURES 3A and 3B depict a flow diagram of a method
for automated disambiguation in greater detail;

15 FIGURE 4 illustrates an example flow diagram of a
method for automated disambiguation by record name; and

FIGURE 5 depicts an example flow diagram of a method
for automated disambiguation by record address.

DETAILED DESCRIPTION OF THE INVENTION

Preferred embodiments of the present invention are illustrated in the figures, like numerals being used to refer to like and corresponding parts of the various
5 drawings.

Telephone companies typically have directory assistance systems allowing for callers seeking particular telephone information to receive such information. Callers typically call directory assistance
10 to receive a telephone number for a particular person or business or to locate a corresponding name and address for a telephone number. Generally the caller calls into directory assistance and interacts with a live operator. The operator asks the caller various questions such as
15 the locality (city and state) for the person or business that the caller seeks, the name of the person or business, and possibly the address of the person or business. The caller engages in a dialogue with the operator answering all of the operator's questions until
20 the operator has enough information to perform a database search for the desired telephone number. If the database search returns one record, the operator provides the telephone number to the caller either verbally or more typically by means of a "backend" audio system that
25 utilizes wave files or synthesized human speech. If the database search returns more than one record, the operator asks the caller additional questions in order to eliminate all but the desired returned record. Once the operator has determined the desired returned record, the
30 operator provides the telephone number to caller.

Operator assisted directory assistance systems, while efficient at locating the desired record and providing a positive caller experience, are costly to the telephone companies due to the costs involved with the operator time and man-power required to interact with the callers. Callers expect a quick response when calling directory assistance and do not like to wait or be put on hold. Hence, there must be enough operators working at all times of the day to insure that the majority of callers can quickly and easily speak with an operator and find the desired telephone number.

In order to increase efficiency and defray some of the costs associated with directory assistance systems, telephone companies have begun to automate various aspects of the directory assistance systems using a variety of automation techniques. Initially, telephone companies adopted store and forward technology to record the response of a caller and playback the response to an operator. For instance, a prerecorded prompt asked a caller for the city and state for the desired telephone number. The caller speaks the city and state and the store and forward technology records the caller's response. The recorded city and state is then played for the operator and the caller is transferred to the operator so that the operator can ask the caller additional questions about the desired telephone number, perform the search for the telephone number, and provide the telephone number to the caller.

Telephone companies further automated directory assistance systems with the use of speech recognition capabilities. As with store and forward, the directory

assistance system uses a prerecorded prompt to ask the caller for the locality and the caller speaks the city and/or state. If the directory assistance system successfully recognizes and understands the caller's
5 utterance, the caller's utterance is recorded and another prerecorded prompt plays asking the caller for the listing name. When the caller speaks the listing name, the directory assistance system records the listing name, populates an operator screen with the recognized
10 locality, and plays back to the operator the recorded listing name. The caller is then transferred to the operator where the caller and operator continue the remaining dialogue and the operator performs a database search and provides the desired telephone number to the
15 caller.

Typically, the directory assistance systems are not completely automated because the callers must still interact with live operators and operators still perform the database searches in order to locate the desired
20 telephone number. In addition, the likelihood of failed speech recognition requires that the directory assistance systems be capable of defaulting to an operator upon such a failure. Generally, the call defaults to a live operator after a failed attempt at speech recognition.
25 In addition, further operator and caller involvement is required when a database search returns more than one record and the operator must disambiguate between the returned records so that the caller receives the desired telephone number.

30 Telephone companies have attempted to increase the automation by utilizing speech recognition deeper into

the operator and caller dialogue. But speech recognition success rates and the callers' opinions towards speech recognition systems have slowed the automation of directory assistance systems utilizing speech
5 recognition. Typically when the directory assistance system utilizing speech recognition does not understand an utterance of the caller, the system asks the caller to repeat the utterance. But callers do not like having to repeat themselves when interacting with speech
10 recognition systems and quickly grow frustrated and dissatisfied with directory assistance systems if they constantly have to repeat themselves. In addition, if the speech recognition is not functioning correctly and the call defaults to the operator, the operator generally
15 does not know what the caller has been trying to accomplish and must re-ask questions that the caller has already answered or attempted to answer when interacting with the automated system utilizing speech recognition. Therefore, the caller becomes even more frustrated and
20 dissatisfied because the caller now has to repeat utterances to the operator.

By contrast, the example embodiment described herein allows for an automated directory assistance system including automated disambiguation strategy of search
25 results utilizing speech recognition. The example embodiment allows for the disambiguation of returned telephone records without the intervention of a live operator. Time and money is saved because operators are no longer required to interact with callers to
30 disambiguate the returned records when more than one record satisfies one or more search terms provided by the

caller with respect to the desired telephone number.
Therefore, employees' and operators' time may be better
utilized in interacting with callers experiencing
difficulties as well as in other revenue generating
5 projects since less man-power is required to disambiguate
returned records in the directory assistance system.

Referring now to FIGURE 1, a block diagram depicts
directory assistance system 10. In the example
embodiment, directory assistance system 10 may include
10 respective software components and hardware components,
such as processor 12, memory 14, input/output ports 16,
hard disk drive (HDD) 18 including databases 20, 22, and
24, and those components may work together via bus 26 to
provide the desired functionality. In alternate
15 embodiments, HDD 18 may contain more than three or less
than three databases. The various hardware and software
components may also be referred to as processing
resources. Directory assistance system 10 may be a
personal computer, a server, or any other appropriate
20 computing device. Directory assistance system 10 may
further include display 28 for presenting operator screen
30 and input devices such as a mouse and a keyboard.
Directory assistance system 10 also includes search
engine 32, disambiguation engine 34, track engine 36, and
25 error engine 38, which reside in memory such as HDD 18
and are executable by processor 12 through bus 26.
Directory assistance system 10 may further include an
automated speech recognition (ASR) engine and a text to
speech (TTS) engine that enable directory assistance
30 system 10 to utilize a speech recognition interface with
the callers. The ASR engine allows directory assistance

system 10 to recognize the speech or utterances provided by the callers in response to prompts while the TTS engine allows directory assistance system 10 to playback to the callers in prompts variable data, such as data
5 returned from a database search.

Display 28 presents operator screen 30 which allows for the input of various search terms into directory assistance system 10 to automatically disambiguate and for automated departure to an operator upon an error.
10 Shown in FIGURE 1 is an example operator screen 30. Operator screen 30 includes seven information fields 40, 42, 44, 46, 48, 50, and 52 allowing for the individual input of various specific caller utterances and search terms such as locality (city field 40 and state field
15 42), name (last name field 44, first name field 46, business name field 48, and government name field 50), and address field 52. In alternate embodiments, operate screen 30 may include more than seven or less than seven information fields and the information fields may be for
20 different information than those shown in FIGURE 1.

The callers interface with directory assistance system 10 using telephones 56, 58, and 60. Telephones 56, 58, and 60 communicate with directory assistance system 10 via network 54 and I/O port 16. Network 54 may
25 be a public switched telephone network, the Internet, or any other appropriate type of communication network. Although three telephones 56, 58, and 60 are shown in FIGURE 1, in alternate embodiments directory assistance system 10 may interface with more than three or less than
30 three telephones.

Directory assistance system 10 allows for the automated searching and returning of telephone directory information such as telephone numbers, listing names, and listing addresses. Although the example embodiment is described in reference to automated speech recognition as the interface between directory assistance system 10 and the callers, in alternate embodiments the callers may also interface with directory assistance system 10 utilizing touch-tone input, a combination of speech recognition and touch-tone, or any other appropriate method of interfacing.

FIGURES 2A and 2B illustrate a flow diagram of a method for the automated disambiguation of search results in directory assistance system 10 and automated defaulting to an operator within directory assistance system 10. FIGURES 3A, 3B, 4 and 5 provide more detail with respect to the automated disambiguation strategy. FIGURES 2A and 2B may be referred to collectively as FIGURE 2, and FIGURES 3A and 3B may be referred to collectively as FIGURE 3.

The method begins at step 80 and at step 82 a caller accesses directory assistance system 10 by calling a telephone number for directory assistance such as "1+411." In response to the caller dialing directory assistance, a dialog with the caller begins between the caller and directory assistance system 10 utilizing automated speech recognition. At any step, if the speech recognition is not successful, the call defaults to a live operator where such defaulting to the operator is described in greater detail below.

At step 84, directory assistance system 10 prompts the caller by playing a prompt asking the caller if the caller is interested in locating a telephone number where the caller has a name, performing a reverse directory
5 assistance ("RDA") look-up where the caller has a telephone number and wants to determine a corresponding name and address, or if the caller is interested in something else. In response to the prompt, the caller speaks a response or utterance depending on the caller's
10 reason for calling directory assistance. For example, if the caller is interested in finding a telephone number, the caller says "telephone number" in response to the prompt. Whenever the caller responds to any prompt, track engine 36 tracks and stores the caller's response
15 or utterance in database 24. For example, if at step 84 the caller's utterance is "telephone number" in response to the prompt, track engine 36 stores "telephone number" in database 24.

If at step 84 the caller responds that he is
20 interested in an RDA look-up, then at step 86 directory assistance system 10 prompts the caller for the telephone number including area code. The caller speaks the telephone number and directory assistance system 10 confirms the telephone number. Once directory assistance
25 system 10 successfully recognizes the ten digit telephone number, at step 88 directory assistance system 10 accesses and searches D1 database 20 in order to locate a name and address that correspond with the telephone number provided by the caller. D1 database 20 is a real
30 world directory of names, addresses, and telephone numbers for individuals, businesses, and the government

created and maintained by Nortel Networks Limited.
Whenever a search is performed in D1 database 20, the
search terms used to search D1 database 20 have already
been successfully recognized utilizing an ASR engine.

5 Although D1 database 20 is shown within directory
assistance system 10 in the embodiment of FIGURE 2, in
alternate embodiment D1 database 20 may be remotely
located remotely with respect to directory assistance
system 10 and accessed via a network connection.
10 Furthermore, directory assistance system 10 may search
other name, address, and telephone number databases in
place of or in addition to D1 database 20.

If at step 88 directory assistance system 10 locates
a corresponding name and address, directory assistance
15 system 10 checks a non-publication list and if the
telephone number is not on the non-publication list
provides the name and address to the caller. The non-
publication list is a list of telephone customers who
have paid a fee so that their name, address, and
20 telephone number will not be given out to callers by
directory assistance. Before directory assistance system
10 provides any telephone information to the caller,
directory assistance system 10 must always first check to
see if the information is for an entity that is on the
25 non-publication list. If the telephone number is on the
non-publication list, directory assistance system 10
informs the caller that the owner of the telephone number
has requested that their information not be provided and
therefore does not provide the corresponding name and
30 address to the caller. If there is no corresponding name
and address, directory assistance system 10 informs the

caller that no name and address matches the telephone number provided and directory assistance system 10 may end the call, provide a different telephone number, or default to the operator.

5 If at step 84 the caller wants something else besides a telephone number or a RDA look-up, track engine 36 tracks and stores the caller's utterance and then the caller is transferred to a live operator so that the operator may assist the caller with the inquiry.

10 If the caller wants to find a telephone number at step 84, then at step 92 the caller is prompted for the locality of the entity for which the caller seeks the telephone number. Depending on what information number the caller calls, the caller may be prompted for both the
15 city and state or just the city. The caller responds to the prompt for locality by speaking the city and/or state and track engine 36 tracks and stores the caller's utterance. At step 94, directory assistance system 10 must determine if the search for the telephone number is
20 going to initially proceed through frequency requested database ("FRL") database 22 using only a name provided by the caller or if directory assistance system 10 prompts the caller for additional information regarding the type of entity for the telephone number sought such
25 as residential, business, or government ("RBG") before searching FRL database 22.

 FRL database 22 is a database created and maintained by directory assistance system 10. FRL database 22 includes telephone listings that are frequently requested
30 by callers accessing directory assistance. Directory assistance system 10 monitors the records provided to the

callers and how frequently each record is requested by the callers in order to determine a frequency of request for each record. The records requested the most are stored in FRL database 22 for quick access and thereby
5 allow directory assistance system 10 to quickly and easily provide the telephone number to the caller when the caller requests information for a record in FRL database 22. In the embodiment shown in FIGURE 2, FRL database 22 is located within directory assistance system
10 10. In alternate embodiments, FRL database 22 may be remotely located with respect to directory assistance system 10 and accessed via a network connection.

FRL database 22 may be partitioned with respect to the record type in order to shorten search times. For
15 example, records for businesses may be stored in one partition of FRL database 22 while records for government listings may be stored in a different partition of FRL database 22. This allows for quicker search times when search engine 32 has the record type as one of the search
20 terms. If search engine 32 is looking for a business listing, search engine 32 searches just the business record partition of FRL database 22 and only searches the business records in FRL database 22. Therefore time is not wasted searching the government records when
25 directory assistance system 10 is already aware that the caller is only interested in a telephone number for a business entity.

When records are added to FRL database 22, directory assistance system 10 adds an indicator to each record to
30 indicate whether the name in the record is for a family name, a business name, a department name, or any other

appropriate type of name pertaining to a telephone listing. In addition, FRL database 22 may only include business and government listing records and not residential listing records due to callers generally
5 requesting a telephone number for a business or government entity when accessing directory assistance and infrequently requesting a residential telephone number.

Whether directory assistance system 10 follows the FRL route or the RBG route depends on the goals and level
10 of caller satisfaction desired by the owner and operator of directory assistance system 10. The RBG route allows for an additional caller prompt versus the FRL route where the additional prompt extracts from the caller if the desired telephone number is for a business,
15 government office, or residence. With the additional information, search engine 32 has a narrower search space, a quicker search, and returned records that are more likely to correctly satisfy the search terms. For example, the caller is prompted for business,
20 residential, or government. If the caller responds "business," then search engine 32 searches only the business partition of FRL database 22 and does not search any of the government or residential records. Typically caller satisfaction decreases with each additional prompt
25 that the caller has to respond to. Therefore the RBG route trades lower caller satisfaction for quicker and more accurate searches.

The FRL route, on the other hand, offers one less prompt versus the RBG route which correlates to greater
30 caller satisfaction but less accurate searching. The FRL route prompts the caller for the desired name and begins

a search for records matching the provided name without asking the caller if the name is for a business, government office, or a residence. Because the FRL route includes one less prompt than the RBG route, search engine 32 has less search terms to search with (name only and no entity type) and therefore the search space is much broader than the search space in the RBG route. For example, search engine 32 searches both the business and government partitions of FRL database 22 for the name provided by the caller. The larger search space and fewer search terms result in a greater chance of returning a returned record that does not correctly satisfy the search terms. The FRL route and RBG route allow for owners and operators of directory assistance systems to customize their directory assistance systems with respect to their callers and business goals based on caller satisfaction levels, search times, and accuracy of searches.

If at step 94 directory assistance system 10 follows the FRL route, then at step 96 the caller is prompted for the name of the entity for which the caller desires the telephone number. Track engine 36 stores the caller's utterance regarding the name and at step 98 search engine 32, using the name provided by the caller as well as the locality information provided by the caller at step 92 as search terms, searches FRL database 22 for any records that satisfy the name and locality provided by the caller.

At step 100, search engine 32 returns a number of records that satisfy the search the terms. The number of returned records can be zero, one, or more than one where

a returned record is a record satisfying the search terms including a single name and single telephone number. If a returned record includes a name followed by departments or divisions each having a unique telephone number, then
5 that returned record is considered as more than one returned record. For example, if a search for "Steve's Grocery" returns the following record, the returned record for "Steve's Grocery" is considered as more than one returned record because of the multiple names and
10 telephone numbers.

Steve's Grocery	549 Bull Creek	512-555-2522
Deli		512-555-2533
Produce		512-555-2544

15

If only one record satisfies the search terms at step 100, then at step 102 directory assistance system 10 checks to see if the returned record is on any non-publication lists and if not, provides the telephone
20 number for the returned record to the caller. In addition to the telephone number, directory assistance system 10 may also provide the name and address of the returned record to the caller. For instance, if the caller wanted the number for "Bob's Wholesale Tools,"
25 when providing the telephone number directory assistance system 10 may provide the telephone number by stating, "The telephone number for Bob's Wholesale Tools at 2341 54th Street is 555-1475." Providing the name and address in addition to the telephone number implicitly confirms
30 to the caller that he is receiving the correct telephone number especially in situations where the caller has not

provided any address information. Furthermore, it provides assurances to the callers who are sometimes uneasy in dealing with fully automated systems because they know they are getting the correct telephone number
5 for the right location.

If at step 100 search engine 32 returns more than one record satisfying the search terms, then the process continues to FIGURE 3 where directory assistance system 10 automatically disambiguates the returned records.
10 This process is described below in greater detail with respect to FIGURES 3, 4, and 5.

If at step 100 search engine 32 finds zero records satisfying the search terms, then search engine 32 accesses and searches one or more name databases in order
15 to locate a name corresponding with the name provided by the caller at step 96. The name databases include names only and do not include any telephone listing information such as telephone number or address. Such telephone information changes frequently and therefore it is very
20 expensive to constantly update databases containing both names and telephone information. But name information changes less frequently and therefore it is relatively inexpensive to frequently update the name information in the name databases. Search engine 32 utilizes the name
25 databases as grammars when recognition of the name supplied by the caller fails using FRL database 22.

At step 104 search engine 32 accesses a database containing only business names (and not business listings) and searches for any business names satisfying
30 the name provided by the caller at step 96. If search engine 32 locates a business name matching the name

provided by the caller, then the process proceeds to step 110. If search engine 32 does not find any business names matching the name provided by the caller, then at step 106 search engine accesses a database containing
5 only government names (and not government listings) and searches for any government names that match the name provided by the caller at step 96. If search engine 32 locates a government name that matches the name provided by the caller, then the process continues to step 110.
10 But if search engine 32 does not locate any government names matching the name supplied by the caller, then at step 108 search engine 32 accesses a database containing only residential names (and not residential listings) and searches for any residential names that matches the name
15 provided by the caller. If search engine 32 locates a residential name then the process continues to step 110. If search engine 32 does not locate a residential name that matches the name provided by the caller at step 108, then the call defaults to a live operator where the
20 procedure for defaulting to a live operator is described in greater detail below.

At step 110, search engine 32 has located a name that matches the name provided by the caller at step 96. Depending on the desired level of automation, at step 110
25 the caller may default to a live operator or continue interacting with directory assistance system 10. If the caller switches to the live operator, then the live operator assists the caller in locating the desired telephone number and such procedure is described below.

30 If the caller does not switch to the live operator, then at step 112 search engine 32 accesses and searches

D1 database 20 using the name located at step 104, 106, or 108 as the search term. D1 database 20 includes the majority of telephone listings and not just the most frequently requested listing like FRL database 22 so when
5 a search of FRL database 22 does not return any records, a search of D1 database 20 has a greater probability of returning a record. At step 114, search engine 32 determines how many returned records satisfy the search term. If the search of D1 database 20 returns no
10 returned records, then the call defaults to the live operator and the operator assists the caller as described below. If search engine 32 locates more than one returned record, then directory assistance system 10 automatically disambiguates the returned records as
15 described in FIGURES 3, 4, and 5. If search engine 32 locates one returned record, then at step 116 directory assistance system 10 provides the telephone number to the caller in the same manner as described above so long as the returned record is not listed on a non-publication
20 list.

If at step 94 directory assistance system 10 follows the RBG route, then at step 118 directory assistance system 10 prompts the caller to determine if the telephone number the caller is seeking is for a business,
25 a residence, or a government office and the caller provides an utterance in response to the prompt. If the caller utters "business," then at step 120 directory assistance system 10 prompts the caller for the business name. If the caller utters "government," then at step
30 122 directory assistance system 10 prompts the caller for the government name. If the caller utters "residential,"

then at step 124 directory assistance system 10 prompts the caller for the first and last name of the person for whom the caller seeks the telephone number.

Where the caller desires a business or government
5 number, then at step 125 search engine 32 accesses FRL database 22 and searches FRL database 22 for the business or government name provided in step 120 or 122. At step 125 search engine 32 searches only a partition of FRL database 22. If the caller desires a telephone number
10 for a business, then search engine 32 searches only the business partition of FRL database 22. If the caller desires a telephone number for a government entity, then search engine 32 searches only the government partition of FRL database 22. If the caller seeks a residential
15 telephone number, then the process continues to step 110 where the caller is either transferred to a live operator or remains in the automated system where search engine 32 accesses and searches D1 database 20 at step 112 for the first and last name provided by the caller at step 124.
20 The caller then continues to step 114 as described above. In alternate embodiments, FRL database 22 includes telephone numbers for residential telephone numbers in addition to business and government listings and a search for the residential first and last name may also be
25 performed in FRL database 22 at step 125 instead of D1 database 20 at step 112.

Search engine 32 searches FRL database 22 for the entity type and name provided by the caller. At step 126, search engine 32 determines how many returned
30 records from FRL database 22 satisfy the search terms. If search engine 32 locates zero returned records, then

the process continues to step 110 as described above. If search engine 32 locates more than one returned record, then directory assistance system 10 automatically disambiguates the returned records as described with respect to FIGURES 3, 4, and 5. If search engine 32 locates one returned record satisfying the search terms, then at step 128 directory assistance system 10 provides the telephone number and corresponding information to the caller unless the returned record is listed on a non-publication list.

FIGURES 3, 4, and 5 illustrate a method for automated disambiguation when search engine 32 locates more than one returned record satisfying the search terms. FIGURE 3 depicts a flow diagram of the method for automated disambiguation in greater detail. FIGURE 4 illustrates an example flow diagram of a method for automated disambiguation by record name. FIGURE 5 depicts an example flow diagram of a method for automated disambiguation by record address.

There are many different forms or types of records each having one or more data fields. One record type is a stand-alone or straight line record which includes a name (first and last), address, and telephone number. An example stand-alone record is "Smith, John, 1213 Main Street, 512-555-1234." For the above record, the name data field is "Smith, John" and the address data field is "1213 Main Street." More specifically, "Smith" is the Name1 data field which is for the family name on a residential record and "John" is the Name2 data field which is for the given name on a residential record. Another record type is a straight line under set record

which includes both a parent record and one or more child or subordinate records where both the parent record and the child records each have a telephone number. An example straight line under set record is as follows:

5

Johnson Auto Mart	2715 N. Umbridge	512-555-8700
Sales		512-555-8710
Service		512-555-8720
Trucks		512-555-8730
Used Cars	2750 N. Umbridge	512-555-8740

10

where "Johnson Auto Mart" is the parent record and "Sales," "Service," "Trucks," and "Used Cars" are the child or subordinate records. Yet another type of record is a caption set record which includes both a parent record and one or more subordinate records but the parent record does not have a telephone number associated with it and each subordinate record does have a telephone number. An example caption set record is as follows:

15

20

Smith Foods

Store No. 1	125 Main Street	512-555-8500
Store No. 2	7865 Pine	512-555-9514
Store No. 3	7895 N. Research	512-555-7532

25

The records are analyzed based on hierarchical levels. The stand-alone and parent level is referred to as Level 0. The first child or subordinate level is Level 1 and a subordinate record of a subordinate record is referred to as Level 2. Records at the same hierarchical level are referred to as peer records while

30

peer records that have the same parent record are sibling records. At Level 0, peer records are a combination of stand-alone records and parent records. For the purposes of automated disambiguation, a threshold level or tier
5 may need to be established whereby returned records having a hierarchy level higher than the threshold level or tier will not be subject to the automated disambiguation. For the embodiment shown in FIGURE 3, the threshold level has been set to three levels or tiers
10 of record hierarchy. Shown below are three sample records illustrating the three tiers of records.

Tier One

Parent

Child 1
15 Child 2
Child 3
Child 4

Tier Two

Parent

20 Child 1
Subordinate 1.1
Subordinate 1.2
Child 2
Subordinate 2.1
25 Subordinate 2.2

Tier Three

Stand-Alone 1

Stand-Alone 2

Parent 1

30 Child 1.1
Subordinate 1.1.1

Child 1.2

Subordinate 1.2.1

Subordinate 1.2.2

Parent 2

5 Child 2.1

Child 2.2

Subordinate 2.2.1

Subordinate 2.2.2

Child 2.3

10 Subordinate 2.3.1

With respect to disambiguation and the three levels or tiers, disambiguation occurs first among the parent or stand-alone level, next among the child level, and last among the subordinate level. In alternate embodiments, the number of levels of record hierarchy may be less than three or more than three. The addition of a tier or level requires an additional dialogue or prompt between directory assistance system 10 and the caller and the caller's satisfaction decreases with each additional prompt because the caller is spending longer than the caller desires to spend interacting with an automated system.

For discussion of FIGURES 3, 4, and 5, assume that the caller is seeking information regarding Johnson Auto Mart. Search engine 32 has performed a search of FRL database 22 and/or D1 database 20 using "Johnson Auto Mart" as the search term and returned the following returned records:

30	Johnson Auto Mart	2715 N. Umbridge	512-555-8700
	Sales		512-555-8710

	Service		512-555-8720
	Trucks		512-555-8730
	Used Cars	2750 N. Umbridge	512-555-8740
5	Johnson Auto Mart	325 E. Beanna	512-555-9600
	Parts		512-555-9640
	Service		512-555-9630

The automated disambiguation strategy takes into
10 account the hierarchical structure and relationships of
and among the returned records. Starting at the lowest
level and continuing through successively higher levels,
directory assistance system 10 and disambiguation engine
34 disambiguate among returned records either by a name
15 field or an address field.

When automatically disambiguating between more than
one returned record, disambiguation engine 34 first
determines which one of the stand-alone and parent (Level
0) records is desired by the caller. If the caller's
20 target is a parent record having more than one child
record, disambiguation engine 34 then selects the child
and finally the child's subordinate record if there is
one.

Disambiguation engine 34 attempts to disambiguate a
25 set of returned records by the name field provided each
of the returned records have a name and that name is
unique. If each name is not unique, then disambiguation
engine 34 disambiguates the returned records using the
address data field using street name or street name and
30 building number if each street name is not unique.
Returned records where the name data field identifies the

entity only by store number are not used so that disambiguation would first be by address.

When search engine 32 returns more than one returned record at step 100, 114, or 126, the process continues to
5 step 150 with automated disambiguation. At step 150, disambiguation engine 34 takes the hierarchical level of the topmost record as the initial level (Level 0) on which to disambiguate returned records. For example, disambiguation engine 34 takes "Johnson Auto Mart" as
10 Level 0. In addition, disambiguation engine 34 also checks each returned record to see if any telephone numbers are flagged as the main telephone number. At step 152, disambiguation engine 34 scans each of the returned records in order to determine if the first
15 returned record stands alone or has peers. If there is more than one record at this level, then the process continues to step 154 where the loop count is incremented by one. For example, there are two returned records at Level 0 so the process continues to step 154. If search
20 engine 32 had only returned the first Johnson Auto Mart record, then at step 152 the process would continue to step 158. At step 156 disambiguation engine 34 checks to see if the loop count exceeds four and if it does, the call defaults to a live operator. But if the loop count
25 does not exceed four, then the process continues to step 160.

At step 160, disambiguation engine 34 checks each returned record for particular record information and if found, omits the particular record information from the
30 returned record. For example, disambiguation engine 34 removes from the returned records listings within the

returned records such as "Fax No.," "If No Answer Dial,"
"If Busy Dial," "Toll-Free Dial," or any other
appropriate extra listing information. Disambiguation
engine 34 checks each record for professional designation
5 or name information that indicates a medical or emergency
response personnel or facility and does not omit the
above telephone numbers for those records. At step 162
disambiguation engine 34 determines if omitting returned
record information at step 162 reduces the number of
10 returned records to one. If the number of records is
reduced to one at step 162, then disambiguation engine 34
selects the remaining returned record at step 164 and the
process continues to step 158.

If the number of returned records is not reduced to
15 one at step 162, then at step 166 disambiguation engine
34 checks each returned record to determine if each
returned record has a name in the name data field. If
each returned record does not have a name in the name
data field, then the process continues to step 184. If
20 each returned record does have a name, then at step 168
disambiguation engine 34 checks to see what hierarchical
level the returned records are at. If the level is Level
0, then the process continues to step 172. Given the
example of Johnson Auto Mart, the hierarchical level is
25 Level 0. If the level is greater than Level 0, the
process continues to step 170 where disambiguation engine
34 checks each name to determine if the name is an
allowable name for disambiguation. Some records include
in the name data field a "Store No. XX" or "No. XX" as
30 the name and since generally most callers do not know
individual store numbers, it would not be very helpful to

the caller to disambiguate by store number. Therefore if the name data fields contain non-allowable names such as "Store No.," the process continues to step 184 where disambiguation engine 34 disambiguates the returned
5 records using address or department information.

When all names are allowable, at step 172 disambiguation engine 34 determines if the name in the name data field is unique for each returned record. If each name is unique, then disambiguation engine 34
10 proceeds to disambiguate using the name data field as shown in FIGURE 4. If each record does not have a unique name at step 172, as with Johnson Auto Mart, then the process continues to step 174 where disambiguation engine 34 checks the returned records having identical names in
15 order to determine if the returned records having identical names are duplicate records. If the returned records having identical names are duplicate records, then disambiguation engine 34 retains the first record and discards all other duplicate records. For Johnson
20 Auto Mart the returned records are not duplicative because even though the records have the same name, the records have different addresses and different phone numbers. At step 176, disambiguation engine 34 checks the number of returned records to determine if the
25 duplicative actions taken at step 174 have reduced the number of returned records to one. If the number of returned records is reduced to one, then at step 180 disambiguation engine 34 selects the remaining returned record and the process continues to step 158.

30 If there are still more than one returned records at step 176, at step 178 disambiguation engine 34 checks

again to see if the returned records each have a unique name. If the returned records have unique names, then the process continues to FIGURE 4 where disambiguation engine 34 disambiguates using the name data field. With
5 Johnson Auto Mart the returned records do not have unique names so the process continues to step 182 where disambiguation engine 34 determines if any name occurs more than once among the current set of returned records. If there is more than one name at step 182, then
10 disambiguation engine 34 disambiguates among the returned records using the name data field as shown in FIGURE 4.

For Johnson Auto Mart there is not more than one name at step 182, so the process continues to step 184 where disambiguation engine 34 checks each returned
15 record to determine if each returned record has an address. If each returned record does not have an address, then at step 184 the call defaults to a live operator. But if each returned record has an address, then at step 186 disambiguation engine 34 determines if
20 each returned record has a unique address. Disambiguation engine 34 determines if each address is unique by looking at both the street name and building number of the address data field. For Johnson Auto Mart, each returned record has a unique address because one
25 Johnson Auto Mart is located at 2715 N. Umbridge and the other one is located at 325 Beanna. Therefore, the process continues to step 194 of FIGURE 5. If the returned records do not have unique addresses at step 186, then at step 188 disambiguation engine 34 checks
30 each returned record to determine if the returned records having the same address are duplicates and can therefore

be eliminated as was done above with respect to duplicate names. At step 190 disambiguation engine 34 determines the number of returned records remaining after eliminating any duplicate returned records if only one
5 returned record is left, disambiguation engine 34 selects that returned record at step 192. If at step 190 more than one returned record remains, then the process continues to step 194 of FIGURE 5.

At step 194 disambiguation engine 34 loads one or
10 more grammars for speech recognition into directory assistance system 10 for the locations for each returned record at the current hierarchical level. The grammars allow for an ASR engine to recognize the correct response to a prompt provided by the caller. For instance, if the
15 caller is to select a business on Elm Street or Main Street by speaking the desired street name, the grammars allow the ASR engine to determine if the caller utters "Elm" or "Main." Disambiguation engine 34 checks each of the returned records for a main number at step 196 and if
20 disambiguation engine 34 locates a main number, the phrase "main number" is also added to the grammars at step 198 so that the ASR engine will correctly recognize "main number" if the caller requests the main telephone number.

25 Disambiguation engine 34 begins playing the disambiguation prompts to the caller at step 200. At step 200, disambiguation engine 34 checks the number of returned records at the current hierarchical level and at step 202 checks to determine if the returned records are
30 on the same street or are on different streets. If the returned records are on different streets, then at step

206 disambiguation engine 34 checks the hierarchical level and proceeds to step 208 if the hierarchical level is Level 0 or Level 1. If the returned records are on the same street, then at step 204 disambiguation engine
5 34 plays a prompt and the caller hears a prompt such as, "There are two locations on Main Street." If the returned records are on different streets, as with Johnson Auto Mart, then at step 208 disambiguation engine 34 plays a prompt and the caller hears, "There are two
10 locations for Johnson Auto Mart." At step 210 if the caller provides any response or utterance other than an affirming response ("Yes") to the playing of the entity name, here Johnson Auto Mart, the call defaults to a live operator.

15 After step 204 and if the caller is silent or affirms at step 210, the process continues to step 212 where disambiguation engine 34 determines the number of returned records to disambiguate. How disambiguation engine 34 presents and disambiguates the returned records
20 to the caller depends on the number of returned records using a low threshold and a high threshold. In the embodiment shown in FIGURE 5 (as well as FIGURE 4), the high threshold is set at five returned records and the low threshold is set at two or three returned records.
25 Switch 214 allows disambiguation engine 34 to vary the low threshold. In the example embodiment disambiguation engine 34 can vary the low threshold between two and three. In alternate embodiments, the high threshold may be higher or lower than five and the low threshold maybe
30 lower than two or higher than three.

If there are more than five returned records at step 212, then disambiguation engine 34 prompts the caller for additional information at step 216. Since disambiguation is occurring by address, at step 216 disambiguation engine 34 prompts the caller for the street name for the listing the caller is desiring. For example, if there are six listings for Bob's Wholesale Tools and the caller wants the telephone number for the location on Elm Street, at step 216 disambiguation engine 314 prompts the caller for the street name and the caller responds with "Elm Street." At step 218 disambiguation engine 34 receives the additional information from the caller utilizing speech recognition and at step 220 determines if the street name provided by the caller is a unique location corresponding with one of the returned records.

If the street provided by the caller is unique, then disambiguation engine 34 selects the returned record having the street name matching the street name provided by the caller at step 192. If the street name provided by the caller is not a unique location among the returned records, then the process returns to step 194 and the steps following step 194 are repeated with respect to the street name provided by the caller until there is a successful disambiguation or until the call defaults to the operator. If the street name provided by the caller at step 218 does not match any of the street names of the returned records, the process continues to step 222 where disambiguation engine 34 checks to see if there is a main telephone number. If there is a main telephone number, disambiguation engine 34 provides the main telephone number to the caller at step 224 so long as the main

telephone number is not on a non-publication list. If there is not a main telephone number at step 222, then the call defaults to a live operator.

If the number of returned records at step 212 is
5 between the low threshold and the high threshold, then at step 226 disambiguation engine 34 provides to the caller a pick list of the locations that were loaded in the grammar. Disambiguation engine 34 plays a prompt listing the name and address for each returned record and prompts
10 the caller to pick the desired returned record when the caller hears it by saying "that one." The caller picks the desired returned record at step 228. If the caller hears the desired returned record in the pick list, the process continues to step 192 where disambiguation engine
15 34 selects the returned record selected by the caller at step 228. If the caller does not hear the desired returned record in the pick list, the call defaults to a live operator.

For instance, if there are four returned records for
20 John Smith, disambiguation engine 34 plays the following pick list for the caller: "There are four locations for John Smith. When you hear the one you want, say 'that one:' on Cedar {pause}, on Shoal Creek {pause}, on 30th Street {pause}, or on Congress {pause}." If the caller
25 wants John Smith on Cedar, then after the caller hears "John Smith on Cedar" the caller says "that one" and does not hear the rest of the choices in the pick list. The caller may also say "on Cedar" or "the first one" instead of "that one."

30 If the number of returned records at step 212 is below the low threshold, then at step 230 disambiguation

engine 34 provides the caller a direct choice. For the Johnson Auto Mart example, disambiguation engine 34 plays the following prompt: "Do you want the one on Umbridge or on Beanna" and the caller responds with either

5 "Umbridge" or "Beanna." At step 232 the caller selects the desired returned record by stating the street name of the one the caller wants. When the caller correctly selects a returned record, disambiguation engine 34 selects that returned record at step 192. For example,

10 the caller is looking for the phone number for the Johnson Auto Mart on Umbridge so in response to the prompt, the caller says "Umbridge" and disambiguation engine 34 selects the returned record for Johnson Auto Mart on Umbridge. If the caller does not hear the

15 location that the caller desires or the caller is not aware of more than one location and therefore does not know which location to pick at step 232, then at step 222 disambiguation engine 34 checks to see if there is a main telephone number and provides the main telephone number

20 to the caller at step 224. Since there is no main telephone number for Johnson Auto Mart, if the caller fails the disambiguation at step 232, the call defaults to a live operator at step 222.

Once disambiguation engine 34 selects a returned

25 record, the process returns to step 158. At step 158 disambiguation engine 34 determines if the selected returned record includes any subordinate records. If the returned record has no subordinate records, then the process continues to step 234. But if the returned

30 record has one or more subordinate records, as with Johnson Auto Mart on Umbridge, the process continues to

step 236 where disambiguation engine 34 determines if the parent record has an associated telephone number. If the parent record does not have a telephone number, then the process continues to step 242. If the parent record has
5 a telephone number, as with Johnson Auto Mart, then at step 238 disambiguation engine 34 determines if a main telephone number has already been flagged for the selected returned record. If no main number has been flagged, then at step 240 disambiguation engine 34 flags
10 the telephone number of the parent record as the main number.

Once the main telephone number has been identified and/or flagged, at step 242 disambiguation engine 34 increments the hierarchical level one level, in this
15 example to Level 1, and at step 244 disambiguation engine 34 determines if there are more than one records at hierarchical Level 1. If there is only one record at this hierarchical level, then at step 246 disambiguation engine 34 selects this returned record and the process
20 returns to step 158. If there is more than one record at step 244, as with Johnson Auto Mart, then at step 248 disambiguation engine 34 determines if each of the subordinate records at this level have the same telephone number. If the subordinate records all the have the same
25 telephone number, then disambiguation engine 34 flags the subordinate records as having the same telephone number and the process continues to step 234. If at step 248 the subordinate records do not have the same telephone number, then the loop count is incremented and checked at
30 steps 154 and 156 and the process continues to step 160

where step 160 through step 166 are repeated as described above.

For Johnson Auto Mart on Umbridge, disambiguation engine 34 determines that all the returned records have
5 names at step 166, the names are allowable at step 170, and that the names are all unique at step 172. Since the names are all unique at step 172, the process continues to step 252 and FIGURE 4.

At step 252 disambiguation engine 34 determines the
10 current hierarchical level. If the current level is Level 0, then at step 256 disambiguation engine 34 loads the grammar with the names and the addresses for the peer returned records. If the current level is Level 1, as with Johnson Auto Mart, disambiguation engine 34 loads
15 the grammar with only the names of the peer returned records at hierarchical Level 1 at step 254. At step 258 disambiguation engine 34 checks for a main telephone number and adds the phrase "main number" to the grammars at step 260 if there is a main telephone number. There
20 is a main telephone number for Johnson Auto Mart which is flagged as the main telephone number at step 240.

Disambiguation engine 34 again determines the hierarchical level at step 262 and if the level is not Level 0, disambiguation engine 34 checks for any
25 indicators in the name data field of the returned records at step 264. The "Sales," "Service," Trucks," and "Used Cars" names include department indicators with respect to the name data field so that at step 266 disambiguation engine 34 plays the following prompt to the caller:
30 "There are four departments listed." The name field indicator allows disambiguation engine 34 to know whether

the returned records are for department names,
individuals first or last names, business names, or any
other appropriate name indication. Because the name
indicator is department for Johnson Auto Mart,
5 disambiguation engine 34 uses "department" in the prompt
at step 266. Because the loop count is greater than one
and the caller has already been through one
disambiguation to select the location and is aware of the
returned record entity name, there is no need to provide
10 the entity name at step 270.

Once disambiguation engine 34 plays the prompt and
as long as the caller does not respond (implicit
confirmation) or affirms ("Yes"), the process continues
to step 272. If the caller negates ("No") or says
15 anything else (out of grammar) which would cause
directory assistance system 10 to look up a wrong
listing, the call defaults to a live operator.

At step 272, disambiguation engine 34 determines the
number of returned records and disambiguates in the same
20 manner as described with respect to steps 212 through
232. If the number of returned records is below the low
threshold determined using switch 275, then at step 274
disambiguation engine 34 provides the caller a direct
choice between the returned records. If the caller hears
25 the desired returned record at step 274 and successfully
selects it at step 276, then disambiguation engine 34
selects the desired returned record at step 193. If the
caller does not successfully select the desired returned
record at step 276, then at step 278 disambiguation
30 engine 34 checks for a main telephone number and provides
the main telephone number to the caller at step 280 if

there is a main telephone number or defaults to a live operator if there is not a main telephone number.

If the number of returned records at step 272 is greater than the high threshold, then at steps 282 and
5 284 disambiguation engine 34 requests additional information from the caller in order to determine which returned record is desired by the caller. If the caller provides additional information (such as one of the names loaded in the grammar) that allows disambiguation engine
10 34 to determine which returned record is desired by the caller at step 284, then disambiguation engine 34 selects the desired returned record at step 193. If the caller does not provide additional information that allows disambiguation engine 34 to select the desired returned
15 record at step 284, disambiguation engine 34 checks for a main telephone number at step 278 and provides the main telephone number if there is one at step 280 or defaults to a live operator if there is not a main telephone number.

20 If the number of returned records is between the low and the high threshold, then disambiguation engine 34 provides a pick list based on the names that were loaded in the grammar. At step 286 disambiguation engine 34 plays each name followed by a pause. The pause allows
25 for time for the caller to select the desired returned record. For Johnson Auto Mart for example, disambiguation plays the following prompt: "When you hear the one you want, say 'that one:' Sales {pause}, Service {pause}, Trucks {pause}, or Used Cars {pause}." At step
30 288 the caller responds with "that one" when the caller hears the department that the caller is interested in.

If the caller wants the telephone number for service, then after the caller hears "Service," the caller says "that one," "Service," or "the second one."

Disambiguation engine 34 recognizes the caller's response
5 and selects the returned record at step 193 correlating to the caller's response. If the caller does not successfully pick a returned record from the pick list, the call defaults to a live operator.

Once disambiguation engine 34 selects the desired
10 returned record at step 193, the process returns to step 158 where disambiguation engine 34 determines if the selected returned record has any subordinate records. If the caller desired the number for the Service Department at Johnson Auto Mart then that returned record has no
15 subordinate records and the process continues to step 234.

At step 234, disambiguation engine 34 determines if there is a parent record for the selected returned record and if so, if the parent record is flagged as the main
20 telephone number. With Johnson Auto Mart, the parent record is flagged as the main telephone number so at step 290 disambiguation engine 34 checks if all the subordinate records have the same telephone number. If the subordinate records all have the same telephone
25 number, disambiguation engine 34 offers the caller the main number at step 292 and plays the main telephone number for the caller (if not on a non-publication list) at step 294 if the caller responds that he wants the main telephone number. If the caller does not want the main
30 telephone number at step 292, then disambiguation engine

34 provides the telephone number selected at step 193 to the caller at steps 296 and 298.

If at step 290 the subordinate records do not have the same telephone number, as with Johnson Auto Mart, then at step 300 disambiguation engine 34 determines if the number of subordinate records is greater than one. If there are more than one subordinate records at step 300, then at step 302 disambiguation engine 34 provides the telephone number to the caller for the returned record selected at step 193 as long the returned record is not on a non-publication list. If there is only one subordinate record at step 300, at step 304 disambiguation engine 34 offers the caller the option of the main telephone number or the telephone number for the one subordinate record. If the caller wants the main telephone number, disambiguation engine 34 plays the main telephone number at step 306 so long as it is not on a non-publication list. Disambiguation engine 34 plays the subordinate record telephone number at step 302 if the caller does not want the main telephone number at step 304.

The disambiguation process occurs instantaneously with respect to the caller. When the caller calls directory assistance and states that he wants the number for Johnson Auto Mart, the next prompt the caller hears is "There are two locations for Johnson Auto Mart. Do you want the one on Umbridge or on Beanna?" When the caller responds "Umbridge," the next prompt the caller hears is "There are four departments listed. When you hear the one that you want, say 'that one:' Sales {pause}, Service {pause}, Trucks {pause}, or Used Cars

{pause}." The caller responds "that one" after hearing "Service" and the next prompt the caller hears is "The telephone number for the Service department for Johnson Auto Mart on 2715 N. Umbridge is 512-555-8720." When
5 providing the desired telephone number and corresponding location, the building number for the location may be included if there are two or more locations on the same street.

Despite the ease of use of directory assistance
10 system 10 and the automated disambiguation strategy, there are instances when a caller experiences difficulty in dealing with directory assistance and needs the assistance of a live operator. Directory assistance system 10 incorporates automated procedures for
15 defaulting to a live operator when a caller experiences particular errors within directory assistance.

Throughout all the process described above, track engine 36 tracks and stores in database 24 each utterance spoken by the callers interacting with directory
20 assistance. In addition, error engine 38, in association with track engine 36, determines when an utterance spoken by the caller initiates an error condition. Upon the occurrence of the error condition, error engine 38 puts the caller on hold, connects to a live operator, plays
25 for the operator the utterance causing the error condition (the error utterance) and the utterance preceding the error utterance (the preceding utterance), and then the operator is connected to the caller.

As shown in FIGURES 3, 4, and 5, there are instances
30 when the caller fails to successfully respond to a disambiguation prompt and the call defaults to the

operator. In addition to those instances, error engine 38 also allows for the call to default to the operator when the caller fails to successfully reply to any prompt at any stage within directory assistance.

5 Directory assistance system 10 utilizes speech recognition to interact with the callers. When a caller provides input using speech, the speech recognition software recognizes the caller's utterance with a certain degree or level of confidence. Caller's utterances can
10 be recognized with a high level of confidence, a medium level of confidence, and a low level of confidence. Unique methods may be used to establish and maintain the threshold levels for what is the high confidence level, the medium confidence level, and the low confidence
15 level. Callers' utterances recognized with a medium or low level of confidence may be enough for error engine 38 to transfer the callers to the operator. When track engine 36 tracks and stores each utterance, track engine 36 may also store the confidence level with which the
20 utterance was recognized.

When the caller provides an utterance, track engine 36 stores the utterance in database 24 and error engine 38 monitors the utterance to determine if the utterance causes an error condition. An error condition is an
25 event causing an error in interacting with directory assistance and results in the caller transferring to a live operator. Error engine 38 has different requirements for what types of caller utterances will cause an error condition and caller utterances in
30 response to a prompt may be in error for different reasons. For example, a caller might say nothing in

response to a prompt (TO - no speech time out), begin speaking before the prompt is done playing (STE - spoke too early), speak for so long that there is too much speech for the speech recognition software to recognize (TMS - too much speech), say something that the speech recognition software cannot understand (OOG - out of grammar), or try to respond using touch-tone input instead of speaking (TTD - touch tone digit). An error condition occurs on the occurrence of any permutation of two TO or STE results or on the single occurrence of a TMS, a TTD, or an OOG result. For example, directory assistance system 10 prompts the caller for residential, business, or government and the caller presses buttons trying to spell business in response to the prompt. Error engine 38 recognizes this as a TTD result and defaults the caller to the operator. In alternate embodiments, additional events or conditions as well as various permutation and numbers of errors may cause an error condition.

When the caller satisfies an error condition either as described above or within the disambiguation process as shown in FIGURE 3, 4, and 5, at step 130 error engine 38 populates operator screen 30 with the caller's utterances spoken before the error utterance that were recognized with high confidence. For example, at step 120 directory assistance system 10 cannot understand the caller's utterance in response to the prompt for business name. Error engine 38 recognizes this as a condition satisfying an error condition and therefore transfers the caller to the operator. But prior to the error at step 120, the caller had successfully interacted with

directory assistance system 10 and provided locality information at step 92 and "business" at step 118. Track engine 36 stored the caller's utterance to the locality prompt and the RBG prompt. Error engine 38 accesses
5 database 24 and populates city field 40 and state field 42 with the information provided by the caller's utterances. Because the caller had made it to step 120 in the automated system, all the caller's utterances up to the error had to have been recognized with a high
10 confidence level. By populating operator screen 30 with information from the caller's utterances recognized with high confidence, the operator knows some of what the caller is seeking and does not have to ask the caller to repeat what the caller has already successfully provided.

15 In addition to populating operator screen 30 with information from the utterances recognized with high confidence, at step 132 error engine 38 plays to the operator the preceding utterance, which was recognized with high confidence and no error, and the error
20 utterance causing the error condition. Playing of both the error utterance and the preceding utterance allows the operator to understand the intention of the caller's inquiry and where the inquiry went wrong without having to re-ask the caller numerous questions the caller may
25 have already answered.

Error engine 38 does not provide the immediately preceding utterance if the preceding utterance is a generic utterance. A generic utterance is an utterance that has little meaning to the operator outside of the
30 prompt to which the generic utterance was in response to. Generic utterances include such utterances as "that one,

" yes,", or "no" when following a pick list or a "which one" prompt or in response to a confirmation prompt. When the immediately preceding utterance is a generic utterance, error engine 38 omits the generic utterance and plays to the operator the error utterance and the most immediately preceding utterance that is not a generic utterance. For instance, the caller is prompted for the locality and responds "Austin." The following prompt asks the caller to say "yes" if Austin is the desired locality. The caller says "yes" and the caller is prompted for business, residential, or government. The caller responds "I need a plumber." The caller's response to the RBG prompt is in error and the "I need a plumber" utterance is the error utterance. The utterance preceding the error utterance is "yes" but since that is a generic utterance, error engine 38 goes back one utterance to "Austin" and plays to the operator: "Austin. I need a plumber."

For an error condition occurring during disambiguation for a pick list, error engine 38 populates operator screen 30 with the search terms provided by the caller and omits and does not play for the operator the "that one" utterance in response to the pick list because it would be meaningless to the operator. For a default during disambiguation for either a direct choice or a request for additional information, error engine 38 populates operator screen 30 with the search terms and plays the error utterance and preceding utterance because both of those utterances will have meaning to the operator since those utterances will not be generic utterances.

In addition to omitting generic utterances, error engine 38 can also combine two utterance into one utterance for operator playback purposes. For example, a prompt may ask for the city, and another prompt for the state. The caller replies with two utterances - one for the city and one for the state. If the both the city and state utterances are recognized with high confidence and no error, then error engine 38 may combine the city and state utterances into one utterance when playing back utterances to the operator on the occurrence of an error condition. For example, the caller is prompted for the city and replies "Austin" and is prompted for the state and replies "Texas." The caller is next prompted for the name and the caller replies "business." The error utterance is "business" and error engine 38 combines the "Austin" utterance with the "Texas" utterance into one utterance and plays "Austin, Texas, Business" to the operator.

In addition to city and state utterances, error engine 38 may also combine a first name utterance and a last name utterance into a single utterance for playback to the operator. For instance, if the caller provides the last name and then the first name in two separate utterances and then an error occurs on the next utterance, error engine 38 plays to the operator the combined first and last name as the preceding utterance.

Before error engine 38 begins to play the error utterance and the preceding utterance to the operator, error engine 38 plays a first tone to the operator to alert the operator that the error utterance and the preceding utterance are preparing to play. Error engine

38 plays a second tone when the error utterance and the preceding utterance finish playing and when error engine 38 is preparing to bring the caller online with the operator. The second tone signals the operator to begin
5 speaking with the caller so that caller does not think the line is dead and therefore hangs up.

Once error engine 38 populates operator screen 30 and plays the error utterance and the preceding utterance for the operator, at step 134 the caller is brought
10 online with the operator and the operator and caller continue the dialogue that the caller started with the automated directory assistance. Before error engine 38 connects the caller to the operator, error engine 38 highlights the information fields 40 - 52 in operator
15 screen 30 that error engine 38 populated with information from the caller's utterances. Error engine 38 also highlights the information fields 40 - 52 in operator screen 30 that need to be filled in with information from the caller before the operator can perform a search for
20 the desired returned record and telephone number.

Therefore, the operator immediately knows what additional information to elicit from the caller. The populated operator screen 30 allows the operator to know what questions the caller has already answered and prevents
25 the operator from asking the caller to repeat answers which callers typically hate to do. In addition, playing the error utterance and the preceding utterance allows the operator to know what the caller is trying to accomplish and where the caller ran into trouble.
30 Because the operator knows all this before the caller connects with the operator, less time is required in the

caller/operator dialogue because the operator knows exactly what questions to ask and does not have to repeat any questions that have already been successfully answered.

5 When the operator has gathered from the caller all the necessary information to perform a search, at step 136 the operator access and searches D1 database 20 and locates zero or one or more returned records. If the operator locates more than one returned record matching
10 the search terms, the operator manually disambiguates at step 138 by asking the caller additional questions and the caller selects the desired returned record. Once the caller has selected the desired returned record, at step 140 the operator provides the telephone number to the
15 caller as long as the returned record is not on a non-publication list.

 For example, when a caller calls directory assistance wanting the number for Auto Tech, the caller is prompted for city locality and the caller responds
20 "Austin." Track engine 36 stores "Austin" in database 24. The caller is prompted for state locality, the caller replies "Texas," and track engine 36 stores "Texas" in database 24. The caller is then prompted for business, residential, or government, the caller replies
25 "business," and track engine 36 stores "business." The caller is prompted for the business name, the caller replies "Auto Tech," track engine 36 stores "Auto Tech," and search engine 32 locates two returned records for Auto Tech - one on Main Street and the other on Elm
30 Street. The caller is offered a direct choice between "Main" and "Elm" and the caller responds with "Oak

Street." Error engine 38 recognizes "Oak Street" as an error utterance and defaults the caller to the operator. But before the caller connects with the operator, error engine 38 plays to the operator "Auto Tech. Oak Street" and populates city field 40 with "Austin," state field 42 with "Texas," and business name field 48 with "Auto Tech." Once the utterances have played and operator screen 30 populated, the operator begins speaking with the caller and assisting the caller with locating the desired telephone number.

Although the present invention has been described in detail, it should be understood that various changes, substitutions and alterations can be made hereto without the parting from the spirit and scope of the invention as defined by the appended claims.